

### THE BEST CONSUMER EXPERIENCE IN VENDING

PRODUCT DISPLAY • VARIETY • CONVENIENCE • RELIABILITY



BEST IN CLASS 45 SELECTIONS 360 UNIT





EXCEEDS ENERGY STAR TIER 3 AND 2013 D.O.E.

CRANE MERCHANDISING SYSTEMS



## ...two times more energy efficient than machines made five years ago -





ENERGY EFFICIENT REFRIGERATION PLATFORM

	kwn per year	increased Operating Costs per Year	
BevMax4	1423		
Competitor A	2042	\$68.27 +43%	
Competitor B	2100	\$74.67 +48%	
5-Year Old Machine	2871	\$159.71 +1029	6



BevMax4 exceeds ENERGY STAR Tier 3 Standards. The only Glass Front to exceed the Department of Energy 2013 Conservation Standards.


Based on the national average cost per kWh in January 2009 of \$0.1103/kWh. Actual energy usage may vary based on environmental conditions.

# Only BevMax4 has been designed to enhance the consumer experience and meet the operational needs of bottlers and vending operators.



### RELIABILITY.

The most reliable, dependable vending solution proven by independent lab tests of 20,000 operating vends; 80,000 vend life-cycles and comprehensive field testing exceeding 238,000 vends.



### VARIETY.

Reduce sold-out column potential. Add more facings of high turnover products. Create more variety to appeal to broad consumer segments and daypart consumption. Make more efficient, bigger case drops.



### EFFICIENCY.

A "shimless" vend mechanism addresses costly labor and service concerns. Load any package in any position. Eliminate loading errors. Load fast with both hands. Bottles remain firmly in place (even if the machine is rocked).



### SPEED.

Who likes to wait in line? BevMax4 delivers product in only 8-seconds. Faster delivery time increases sales; speed of service and customer satisfaction.

## SIMPLIFIED MAINTENANCE

Low profile modular refrigeration platform removes from the front or the back of the machine.





### **SPECIFICATIONS**

### **DIMENSIONS**

72" H x 47" W x 32" D (183cm H x 120cm W x 82cm D)

### WEIGHT

764 lbs. empty (347 kg)

### **ELECTRICAL**

115 VAC, 60Hz, 10.2 amps MDB Level 3 Controller

### REFRIGERATION

134A CFC-Free Refrigerant Gas 1/3 HP Compressor

#### CERTIFICATIONS

UL, CUL, CE, FCC, NOM, CTICK